



SAYFLEX EZ CUT

“Frayless” Braided Monofilament Sleeving

SAYFLEX EZ CUT is a braided monofilament sleeving of polyethylene terephthalate (PET) that provides high coverage and less fray after cutting.

- **lightweight**
- **inert to most chemicals**
- **resistant to fungus**
- **excellent abrasion**
- **cut-through resistance**
- **Meets 41575DN material spec**

SAYFLEX Features:

- Rated for continuous service from -70°C through 125°C and will tolerate short-term exposure up to 230°C.
- Stretches and contracts to accommodate irregular shapes and sizes. A single sleeve size can stretch to encase bundles with diameters up to three times its own I.D.
- Shapes to a snug fit producing a compact bundle with a smooth resilient cover, which prevents snagging during installation in cabinets and equipment.
- Can be flexed repeatedly without losing its physical properties. Its open braid construction affords ventilation, preventing trapping of heat or moisture.
- Naturally slick allowing it to slide easily and quickly over end fittings and connectors, reducing labor cost. Bundled elements move freely within the sleeve reducing strain.
- Resists chafing, abrasion, cut-through, flexure-fatigue, and heat degradation.
- Adds minimal weight, bulk and cost to wire harnesses.

SAYFLEX FR - Physical Properties

PROPERTY	ASTM METHOD	TYPICAL VALUES
Strand Diameter	----	.008"
Tensile Strength, PSI	D-876	75,000
Elongation, %	D-876	20
Melt Temperature, °C	D-2217	260

SAYFLEX FR Availability:

Available in a wide range of diameters ranging from 1/8" through 3 3/4" O.D. SAYFLEX EZ CUT is available in black currently.

Made in the USA

* The above data is informational only and should not be used for specification purposes*